

B400-IP-Camera-Specifications		
	Model	B400
Camera	Image Sensor	1/2.7" CMOS Sensor
	Effective Pixels	2560x1440 (4.0 Megapixels)
	Lens	f=4.0 mm Fixed, F=2.0
	Angle of View	Horizontal: 80°, Vertical: 42°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (100ft)(LED: 18pcs/14mil/850nm)
	Backlight Compensation	Support
Video	Noise Reduction	3D DNR
	Compression	H.264
	Resolution	Mainstream: 2560x1440, 2048x1536, 2304x1296, 1080p, 720p; Substream: 640x360
	Bitrate	Mainstream: 1024Kbps~8192Kbps; Substream: 64Kbps~512Kbps
Audio	Frame Rate	Mainstream@30fps, Substream@6fps
	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	SSL, TCP/IP, UDP, UPNP, NTP, DHCP, DNS, DDNS
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
General	Power Supply	DC12V & PoE (IEEE 802.3af 48V Active)
	Power Consumption	<10W
	Working Environment	-10°C~+55°C (14°F~131°F), Humidity: 10%~90%
	Ingress Protection	IP66
	Dimension	Φ67x186 mm
	Weight	415 g