



## **DMNG PRO Series**

## THE ULTIMATE 3G/4G-LTE VIDEO UPLINK SYSTEM

The AVIWEST DMNG® PRO series is the world's most advanced pocket-sized 3G/4G-LTE live high-quality video uplink system, designed to be used by news-gathering professionals worldwide.

The DMNG® PRO is ultra-compact, robust and highly-portable, and allows for direct camera-mounting using standard V-mount or Gold-plate. Its power and versatility give you the required flexibility to always be "news-ready" by combining any of the following network interfaces:

- 8 embedded 3G/HSPA+/4G-LTE modems
   (with high-efficiency custom antenna array giving faster network acquisition and improved resilience)
- · Built-in WiFi modem
- · 2 auxiliary USB ports
- Dual Gigabit Ethernet for BGAN, Ka-Sat or streaming over LAN

The DMNG® PRO has been designed with ease-of-use in mind, the user-friendly intuitive interface allows any user to broadcast live in 3 simple clicks from either the embedded touchscreen or from the AVIWEST smartphone application.

Wherever the news happens, whatever the networks available, the DMNG® PRO gives you the freedom to shoot with the confidence of delivery.



#### **MAIN FUNCTIONS**

#### LIVE

Send a live broadcast-quality video over any kind of IP based networks: bonded 3G or 4G-LTE networks, WiFi, WiMax, Ethernet or satellite (BGAN, Ka band Sat)

#### STORE

Record high quality video files (up to HD) while streaming live at lower resolution.

### FORWARD

Fast Forward the files from the SD card or a memory stick (video, data,..) to the TV station using the available networks








# **Specifications**

## **DMNG PRO SYSTEM OVERVIEW**



## **DMNG PRO MAIN SPECIFICATIONS**

		DMNG PRO 180	DMNG PRO 140	DMNG PRO 100
Main Functions	Live	Yes	Yes	Yes
iviaii i unctions	Store & Forward	Yes	Yes	Yes
	Return IFB channel	Yes	Yes	Yes
	Tally Light	Yes	Yes	Yes
	Built-in GPS	optional	optional	optional
Input Interfaces	HD/SD-SDI embedded audio (BNC)	Yes	Yes	Yes
input interruces	Composite (BNC)	Yes	Yes	Yes
	Analog Audio L&R (BNC)	Yes	Yes	Yes
	HDMI (1.3)	Yes	Yes	Yes
Other Interfaces	ASI-TS out (BNC)	Yes	Yes	Yes
	Gigabit Ethernet (Streaming, BGAN,)	2	2	2
	USB 2.0 (Store, USB modems,)	2	2	2
	RS232, RS485	Yes	Yes	Yes
	SD Card slot (store)	Yes	Yes	Yes
Networks	3G/4G-LTE build-in Modems	8	4	-
	3G/4G-LTE high efficiency custom antennas	8	4	-
	Additional external USB Modems	2	2	2
	Built-in Wifi with high efficiency custom antenna	Yes	Yes	-
	BGAN	Yes	Yes	Yes
	Ka Band Satellite	Yes	Yes	Yes
	Ethernet	Yes	Yes	Yes
Video Compression	H.264/AVC Main/High Profile level 4	Yes	Yes	Yes
	1080i/p @ 25/29.97 fps	Yes	Yes	Yes
	720p @ 50/59.94 fps	Yes	Yes	Yes
	576i and 480i @ 25/29.97 fps	Yes	Yes	Yes
	Bit rates: 128 Kbps to 10 Mbps	Yes	Yes	Yes
	CBR / VBR / Capped VBR	Yes	Yes	Yes
Audio Compression	HE-AAC; HE-AAC v2	Yes	Yes	Yes
	Dual mono / Stereo	Yes	Yes	Yes
	Bit rates: 32 to 128 Kbps	Yes	Yes	Yes
Configuration	Touch screen	Yes	Yes	Yes
	Web GUI (any devices)	Yes	Yes	Yes
D	Remote configuration (from receiver)	Yes	Yes	Yes
Power Supply	11-24V input XLR 4 pins - hot swap Female (Camera side) V-Mount or Gold Mount plate	Yes	Yes	Yes
	, ,	Yes	Yes	optional
Dimension	Male (Battery side) V-Mount or Gold Mount plate Dimensions	optional	optional	100v120vFFm
Dimensions		245x128x55mm	215x128x55mm	180x128x55mm
	Weight (Kg)	1.16	1.11 2.44	0.92
	Weight (Lb):	2.55	2.44	2.02